

MOBILE DEVICE CHARGING CENTERS

USB & 12-VDC

RVs - BOATS - TRAILERS - TRUCKS
ATVs - GOLF CARTS

5200 Series Euro Style Hidden Screw Assemblies



5.0" w x 3.75" h x 2.0" d
(including 1/4" Quick Tabs)

BLACK - WHITE - IVORY

Standard 2.1A Dual USB*
or, 4.2A / Dual 2.1A USB*
12VDC up to 20A**

Durable Plastic Sockets to power and charge most mobile electronic devices.

* USB dual-port sockets state total amps @ 5V. Optional 4.8 ttl amps @ 5V delivers 2.4A per USB port. Sockets have 6-in 20-gauge pre-stripped wire leads and quick nut. (SPO192 Series 1-pc construction does not require nut or assembly)

** 12VDC socket with quick tabs rated for 10A or 20A plug: 10A circuits require 18-gauge wiring; 20A circuits require 14-gauge wiring.

3/8" spacer(s) may be added to front of assemblies or brackets to adjust depth for shallow-wall applications. All products RoHS Compliant.

SINGLE SOCKET WALL-MOUNT STYLES & ASSEMBLIES

Meets Mobile Phone Standards

Output: 5V 2.4A Dual USB*
or, 4.8A / Dual 2.4A USB*
Input: 12-28VDC up to 20A**

Flame Resistant Nylon UL 94V-0
2.25" w x 2.75" h x 1.5" d
USB Mounting Depth: 1.5 inches
Black - White - Ivory



SP0192 Series



(See Page 2)

Euro Style Hidden Screw Assemblies

Output: 5V 2.1A Dual USB*
or, 4.2A / Dual 2.1A USB*
Input: 12-24VDC up to 20A**

Shallow Depth Walls

3.31" w x 3.75" h x 0.50" d
USB Mounting Depth: 0.50" inches
Black - White - Ivory

5100 Series



SOCKETS - NUTS - SPACERS



SURFACE-MOUNT HOUSINGS

Ideal for Shallow Walls & Compartments



SPO191 Black
Double Housing



Single Housing

Use with 12-VDC and USB Sockets and Caps

USB 2.0 / HDMI EXTENSION CABLES



12VUSB&HDMI

Waterproof IP66 Caps
PAT NO. 8,618,416



12VOTABIPUSB
IP66 Cap Labeled USB



12VOTABIP10 (Label, 12V 120W 10A)
12VOTABIP20 (Label, 12V 240W 20A)



12VOTABCAP10 (Label, 12V 120W 10A)
12VOTABCAP20 (Label, 12V 240W 20A)



SP0145
Double Wall Plate
Powder Coated
Aluminum



SP0181-15
Polypropylene



SP4615-6
Single L Bracket
Powder Coated Aluminum



SIGMA
SWITCHES PLUS

Since 1983



Call (574) 294-5776

Fax 574-294-8744

www.sigmaswitches.com
4703 Wyland Dr, Elkhart, IN 46516

MOBILE DEVICE CHARGING CENTERS

USB
INPUT: 12-28 VDC

RVs - BUSES - BOATS - TRAILERS - TRUCKS



Part Dimensions:
h: 2.75 (69.85 mm)
w: 2.25 (57.15 mm)
d: 1.50 (38.10 mm)

AVAILABLE
2.4A and 4.8A

INPUT: 12-28VDC
OUTPUT: 5VDC 4.8A TOTAL
2.4A EACH PORT

**Overload, Reverse Polarity,
and Ignition Protections!**

Meets Mobile Phone Standards

**FC
COMPLIANT**

SP0192-15-A0311

Charges: 2 phones or 1 phone + 1 tablet

- Output: 5V 2.4 Amp Dual USB
- Input: 12-28 VDC
- FCC Compliant
- Meets Mobile Phone Standards
- Device Protection: Voltage Overload,
- Secondary Internal Fuse & Capacitor
- Reverse Polarity Protection
- Ignition Protection
- Flame Resistant Nylon UL 94V-0
- 1.5 Depth / 6-inch 20-Gauge Wire
- Available: Black, Ivory and White

SP0192-15-A0312

Rapid Charges: 2 phones or 2 tablets

- Output: 5V 4.8 Amp Dual USB
- Input: 12-28 VDC
- FCC Compliant
- Meets Mobile Phone Standards
- Device Protection: Voltage Overload,
- Secondary Internal Fuse & Capacitor
- Reverse Polarity Protection
- Ignition Protection
- Flame Resistant Nylon UL 94V-0
- 1.5 Depth / 6-inch 20-Gauge Wire
- Available: Black, Ivory and White