

MOBILE DEVICE CHARGING CENTERS

USB & 12-VDC

RVs - BOATS - TRAILERS - TRUCKS
ATVs - GOLF CARTS

5200 Series Euro Style Hidden Screw Assemblies



5.0" w x 3.75" h x 2.0" d
(including 1/4" Quick Tabs)

BLACK - WHITE - IVORY

Standard 2.1A Dual USB*
or, 4.2A / Dual 2.1A USB*
12VDC up to 20A**

Durable Plastic Sockets to power and charge most mobile electronic devices.

* USB dual-port sockets state total amps @ 5V. Optional 4.8 ttl amps @ 5V delivers 2.4A per USB port. Sockets have 6-in 20-gauge pre-stripped wire leads and quick nut. (SP0192 Series 1-pc construction does not require nut or assembly)

** 12VDC socket with quick tabs rated for 10A or 20A plug: 10A circuits require 18-gauge wiring; 20A circuits require 14-gauge wiring.

3/8" spacer(s) may be added to front of assemblies or brackets to adjust depth for shallow-wall applications. All products RoHS Compliant.

SINGLE SOCKET WALL-MOUNT STYLES & ASSEMBLIES

Meets Mobile Phone Standards

Output: 5V 2.4A Dual USB*
or, 4.8A / Dual 2.4A USB*
Input: 12-28VDC up to 20A**

Flame Resistant Nylon UL 94V-0

2.25" w x 2.75" h x 1.5" d
USB Mounting Depth: 1.5 inches
Black - White - Ivory



SPO192 Series



(See Page 2)

Euro Style Hidden Screw Assemblies

Output: 5V 2.1A Dual USB*
or, 4.2A / Dual 2.1A USB*
Input: 12-24VDC up to 20A**

Shallow Depth Walls

3.31" w x 3.75" h x 0.50" d
USB Mounting Depth: 0.50" inches
Black - White - Ivory

5100 Series



SOCKETS - NUTS - SPACERS



SURFACE-MOUNT HOUSINGS

Ideal for Shallow Walls & Compartments



Use with 12-VDC and USB Sockets and Caps

USB 2.0 / HDMI EXTENSION CABLES



12VUSB&HDMI

Waterproof IP66 Caps
PAT NO. 8,618,416



12VOTABIPUSB
IP66 Cap Labeled USB

12VOTABCAP10 (Label, 12V 120W 10A)
12VOTABCAP20 (Label, 12V 240W 20A)



Water Shedding



SP0181-15
Polypropylene

SP0145
Double Wall Plate
Powder Coated
Aluminum

SP4615-6
Single L Bracket
Powder Coated Aluminum



SIGMA SWITCHES PLUS

Since 1983



Call (574) 294-5776

Fax 574-294-8744

www.sigmaswitches.com
4703 Wyland Dr, Elkhart, IN 46516

MOBILE DEVICE CHARGING CENTERS

USB
INPUT: 12-28 VDC

RVs - BUSES - BOATS - TRAILERS - TRUCKS



SP0192-15-A0311

Charges: 2 phones or 1 phone + 1 tablet

- Output: 5V 2.4 Amp Dual USB
- Input: 12-28 VDC
- FCC Compliant
- Meets Mobile Phone Standards
- Device Protection: Voltage Overload,
- Secondary Internal Fuse & Capacitor
- Reverse Polarity Protection
- Ignition Protection
- Flame Resistant Nylon UL 94V-0
- 1.5 Depth / 6-inch 20-Gauge Wire
- Available: Black, Ivory and White

SP0192-15-A0312

Rapid Charges: 2 phones or 2 tablets

- Output: 5V 4.8 Amp Dual USB
- Input: 12-24 VDC
- FCC Compliant
- Meets Mobile Phone Standards
- Device Protection: Voltage Overload,
- Secondary Internal Fuse & Capacitor
- Reverse Polarity Protection
- Ignition Protection
- Flame Resistant Nylon UL 94V-0
- 1.5 Depth / 6-inch 20-Gauge Wire
- Available: Black, Ivory and White



Call (574) 294-5776

fax: (574) 294-8744

www.sigmaswitches.com
4703 Wyland Dr, Elkhart, IN 46516